



MACHAKOS UNIVERSITY

University Examinations for 2020/2021 Academic Year

SCHOOL OF ENGINEERING AND TECHNOLOGY

DEPARTMENT OF MECHANICAL AND MANUFACTURING ENGINEERING

FIRST YEAR SPECIAL/SUPPLEMENTARY EXAMINATION FOR

BACHELOR OF SCIENCE (ELECTRICAL AND ELECTRONICS ENGINEERING)

EEE 101: ENGINEERING DRAWING II

DATE: 22/3/2021

TIME: 2.00-4.00 PM

INSTRUCTIONS

1. This paper contains FIVE questions.
2. Answer Question **ONE** and any other **TWO** questions
3. Allow 1½ Hours for question 1 and 45 minutes for each of the other two questions.
4. All dimensions are in millimetres unless otherwise stated.
5. Construction lines should be faint and should not be erased.
6. Accuracy and good line work are essential.

QUESTION ONE COMPULSORY (30 MARKS)

The part drawings of a Machine Vice are shown in **Figure Q1(a) to (e)** . The components of the Machine Vice are assembled as shown in **Figure Q1(f)**. Draw:

- a) **Sectional view of the assembly**, through the plane X-X as shown in the Figure Q1(a) viewed from the front elevation as indicated by the arrow on the Figure Q1(f) Machine vice assembly.
- b) **Top elevation of the assembly** and **End elevation of the assembly** from the end elevation as indicated in Figure Q1(f) Machine vice assembly.

Use first angle projection and do not indicate the dimensions and hidden details.

QUESTION TWO (20 MARKS)

Figure Q2 shows a casting. Draw the sectional view, section XX, and the left side view. Front view is as indicated by the arrow. Indicate the dimensions.

QUESTION THREE (20 MARKS)


- a) Differentiate between clearance fit and transition fit. (2 marks)
- b) A journal bearing consists of a bronze bush of diameter 130mm fitted into a housing and a steel shaft of 60mm diameter, running in the bush, with oil as a lubricant. Determine the working dimensions of (a) bore of the housing (b) bush and (c) shaft. Calculate the maximum and minimum interference or clearance. Assume interference fit, H7/p6 for the bush and housing and normal running fit, H7/f7 for the shaft and the bush. Refer to Tables 1, 2 and 3. (18 marks)





QUESTION FOUR (20 MARKS)

Illustrate by using example sketches how the following features are represented in Engineering drawing: Housing, bush, boss, curved slot, rib, fillet, key, keyway, slot and flat.

QUESTION FIVE (20 MARKS)

- a) Draw a double line sketch of an orthographic pipe network of the single line network shown in **Figure Q5 (a)** (14 marks)
- b) **Figure Q5 (b)** shows Light-sensitive Alarm Project circuit. The circuit detects a sudden shadow falling on the light-sensor and sounds the beeper when this happens. Name **the twelve** devices indicated **1 to 12** in the circuit. (6 marks)








Figure Q5 (a)




Figure Q5 (b)

Table 1 Fundamental tolerances of grades 01, 0 and 1 to 16 (values of tolerances in microns) (1 micron = 0.001 mm)

Diameter steps in mm	Tolerance Grades																	
	01	0	1	2	3	4	5	6	7	8	9	10	11	12	13	14*	15*	16*
Over 30 To and inc 50	0.6	1	1.5	2.5	4	7	11	16	25	39	62	100	160	250	390	620	1000	1600
Over 50 To and inc 80	0.8	1.2	2	3	5	8	13	19	30	46	74	120	190	300	460	740	1200	1900
Over 80 To and inc 120	1	1.5	2.5	4	6	10	15	22	35	54	87	140	220	350	540	870	1400	2200
Over 120 To and inc 180	1.2	2	3.5	5	8	12	18	25	40	63	100	160	250	400	630	1000	1600	2500

Table 2 Fundamental deviations for shafts of types **a** to **k** of sizes upto 500mm (*contd.*)

Fundamental deviation in microns										(1 micron = 0.001 mm)					
Diameter steps in mm		Upper deviation (es)								js ⁺	Lower deviation (ei)				
		a	b	c	d	e	f	g	h		j			k	
over	upto	All grades								± IT/2	5.6	7	8	4 to 7	≤ 3, > 7
50	65	− 340	− 190	− 140	− 100	− 60	− 30	− 10	0		− 7	− 12	—	+ 2	0
65	80	− 360	− 200	− 150											
80	100	− 380	− 220	− 170	− 120	− 72	− 36	− 12	0		− 9	− 15	—	+ 3	0
100	120	− 410	− 240	− 180											
120	140	− 460	− 260	− 200	− 145	− 85	− 43	− 14	0		− 11	− 18	—	+ 3	0
140	160	− 520	− 280	− 210											
160	180	− 580	− 310	− 230											

Table 2 Fundamental deviations for shafts of types **m** to **zc** of sizes upto 500 mm (*contd.*)

Fundamental deviation in microns															(1 micron = 0.001 mm)	
Diameter steps in mm		Lower deviations (ei)														
Over	Upto	m	n	p	r	s	t	u	v	x	y	z	za	zb	zc	
All grades																
30	40	+9	+17	+26	+34	+43	+48	+60	+68	+80	+94	+112	+148	+200	+274	
40	50						+54	+70	+81	+97	+114	+136	+180	+242	+325	
50	65	+11	+20	+32	+41	+53	+66	+87	+102	+122	+144	+172	+226	+300	+405	
65	80				+43	+59	+75	+102	+120	+146	+174	+210	+274	+360	+480	
80	100	+13	+23	+37	+51	+71	+91	+124	+146	+178	+214	+258	+335	+445	+585	
100	120				+54	+79	+104	+144	+172	+210	+254	+310	+400	+525	+690	
120	140	+15	+27	+43	+63	+92	+122	+170	+202	+248	+300	+365	+470	+620	+800	
140	160				+65	+100	+134	+190	+228	+280	+340	+415	+535	+700	+900	
160	180				+68	+108	+146	+210	+252	+310	+380	+465	+600	+780	+1000	

Table 3 Fundamental deviations for holes of types **A** to **N** for sizes upto 500 mm (*contd.*)

A to N

Fundamental deviation in microns																	(1 micron = 0.001 mm)			
Diameter steps in mm		Lower deviations (EI)										Upper deviations (ES)								
		A*	*B	C	D	E	F	G	H	Js+	J			K		M		N		
Over	Upto	All grades								± IT/2	6	7	8	≤ 8	> 8	≤ 8 $\frac{1}{2}$	> 8	≤ 8	> 8*	≤ 7
30	40	+ 310	+ 170	+ 120	+ 80	+ 50	+ 25	+ 9	0		+ 10	+ 14	+ 24	- 2 + Δ	—	- 9 + Δ	- 9	- 17 + Δ	0	Same deviation as for grades > 7 + Δ
40	50	+ 320	+ 180	+ 130																
50	65	+ 340	+ 190	+ 140	+ 100	+ 60	+ 30	+ 10	0		+ 13	+ 18	+ 28	- 2 + Δ	—	- 11 + Δ	- 11	- 20 + Δ	0	
65	80	+ 360	+ 200	+ 150																
80	100	+ 380	+ 220	+ 170	+ 120	+ 72	+ 36	+ 12	0		+ 16	+ 22	+ 34	- 3 + Δ	—	- 13 + Δ	- 13	- 23 + Δ	0	
100	120	+ 410	+ 240	+ 180																
120	140	+ 460	+ 260	+ 200	+ 145	+ 85	+ 43	+ 14	0											
140	160	+ 520	+ 280	+ 210						+ 18	+ 26	+ 41	- 3 + Δ	—	- 15 + Δ	- 15	- 27 + Δ	0		
160	180	+ 580	+ 310	+ 230																